

This is a full synthetic lubricant based on carefully selected very high quality base oils, especially developed for the requirements of Ford WSS-M2C913-C/D specifications. It is characterized by significantly improved lubricating properties and provides Fuel Economy (>3%). This oil replaces the M2C-913-A/B specifications.

## Performance

- ACEA: A1/B1-12
- API: SL/CF
- RENAULT: RN 0700
- ACEA: A5/B5-12
- FORD: WSS-M2C913-C/D
- JAGUAR / LAND ROVER STJR.03.5003

## Features

Fuel economy : superior fuel economy and CO2 reduction.

Total engine protection : performance in keeping the engine clean .

Cold start : excellent fluidity at low temperature .

## Applications

It is mandatory for all Ford models (gasoline and diesel, also those with particulate filter) from 2009 onwards. It's also required for the vehicles equipped with the 2,2 Duratorq TDCI engines and is fully backwards compatible with all current Ford diesel engines, with the exception of the models which are equipped with pump injectors (Galaxy I en II) and Ford KA (diesel and gasoline from 2009).

Characteristics	Unit	Average
Density at 15 °C	kg/l	0.853
Viscosity -20 °C	mPas	4200
Viscosity 40 °C	mm <sub>2</sub> /s	53.30
Viscosity 100 °C	mm <sub>2</sub> /s	9.66
Viscosity index		168
Flash point COC	°C	220
Pour point	°C	-45
Total Base Number	mgKOH/g	10.1
Sulphated Ash	%	1.09