Cars

Trans ATF III H

This is a mineral lubricant based on carefully selected highly refined base oils. This is an oil with a very high viscosity index for most automatic transmissions. The improved fluidity at low temperatures ensures optimum performance in all conditions. Its exceptional frictional characteristics provide smooth switching and driving comfort.

Performance

- ALLISON : C4
- FORD: MERCON
- GM: DEXRON III-H
- MAN: 339 V1/Z1
- MB: 236.5
- MB: 236.1
- VOITH: H55.6335
- VOLVO: 97341
- ZF: TE-ML 09B
- ZF: TE-ML 11B
- ZF: TE-ML 14A

Features

Frictional properties : smooth shift performance.
Anti-wear protection : extended transmission life.
Extended oil life : excellent thermal and oxidation stability.

Applications

This oil is used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron III or Dexron II E and Ford Mercon-requirements.

Characteristics	Unit	Average
Density at 15 °C	kg/l	0.855
Viscosity -40 °C	mPas	17500
Viscosity 40 °C	mm¸/s	33.9
Viscosity 100 °C	mm¸/s	7.1
Viscosity index		179
Flash point COC	°C	196
Pour point	°C	-45
Color		RED