

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting.

## Performance

- AML: 4G4319A509/AA/S    • BENTLEY: PY112995PA
- BMW: 83220142516        • BMW: M-1375.4
- HYUNDAI: 040000C90SG   • JAGUAR: Fluid 8432
- LAND ROVER:  
TYK500050                    • MASERATI: 231603
- VW: G 055 005             • ZF: TE-ML 11

## Features

Anti-wear protection : significantly extended transmission life.

Frictional properties : very smooth gear shifting, no vibration.

Extended oil life : excellent thermal and oxidation stability.

## Applications

Mainly intended for the ZF-6 speed automatic transmissions, as fitted in BMW, Jaguar and Land Rover, it is also suitable for other OEMs, who recommend this type of fluid (e.g. Audi Quattro).

| Characteristics                | Unit               | Average |
|--------------------------------|--------------------|---------|
| Density at 15 °C               | kg/l               | 0.845   |
| Brookfield viscosity at -40 °C | mPas               | 9500    |
| Viscosity 40 °C                | mm <sub>2</sub> /s | 31.0    |
| Viscosity 100 °C               | mm <sub>2</sub> /s | 6.2     |
| Viscosity index                |                    | 153     |
| Flash point COC                | °C                 | 202     |
| Pour point                     | °C                 | -48     |
| Color                          |                    | AMBER   |