Cars

# TRANSMISSION S 75W90

This is a full synthetic lubricant based on carefully selected very high quality base oils, which can be used in a wide field of applications. Because of its special composition, it is particularly suited for synchronized gear boxes, as well as heavily loaded differentials.

## Performance

- API: GL-4 / GL-5
- API: MT-1
- DAF: GL5/MIL-PRF-2105E
- IVECO: VOITH 3.325-340
- MACK: GO-J EO-H
- MAN: 341 E-3 / 341 Z-2 / 342 M-3
- MAN: 3343 /SL 342 S1/342 SL
- MB: 235.6/235.8
- MIL: PRF-2105E
- RENAULT: B0032/3 Annex 3
- SAE: J 2360
- SCANIA: STO 1
- ZF: TE-ML 02B / 05B / 07A / 08 / 12B / 12L / 12N / 16F / 17B / 19C / 21B
- TMS 6816
- DIN 51517

## Features

Frictional properties : very smooth gear shifting, no vibration.
Anti-wear and oxidation stability : superior protection of critical parts.
Extended oil life : excellent thermal and oxidation stability.

## Applications

This oil is recommended for all components of mechanical transmissions (gear boxes, transfer boxes, differentials, etc.). of trucks and four-wheel drive vehicles.

| Characteristics | Unit | Average |
|---|---|---|
| Density at 15 °C | kg/l | 0.869 |
| Viscosity 40 °C | mm¸/s | 101.00 |
| Viscosity 100 °C | mm¸/s | 15.40 |
| Viscosity index | | 161 |
| Flash point COC | °C | 202 |
| Pour point | °C | -50 |
| Total Base Number | mgKOH/g | 2.1 |