Motorcycles

2T Gold

This is a full synthetic lubricant based on carefully selected very high quality base oils for air cooled 2-stroke gasoline engines. This oil is specifically designed for two-stroke engines of motorcycles with mixed or separate lubrication. It assures a remarkable cleanliness of the engine, and has a high lubricity and a high thermal stability. It substantially avoids the formation of exhaust smoke.



Performance

- API: TC
- Piaggio Hexagon
- JASO: FD
- ISO-L-EGD
- JASO: FC
- Husqvarna

Features

Engine protection : outstanding engine cleanliness and durability.
Corrosion protection : adequate corrosion protection.
Smoke suppression : excellent smoke reduction.

Applications

Due to its universal character this lubricant is suitable as well with small displacement engines as with heavy motorcycles. Satifies the requirements of high specific power engines, such as Kawasaki, Suzuki, Yamaha or Honda.

Characteristics	Unit	Media
Densit a 15 ° C	kg/l	0,877
Viscosit -20 ° C	mPas	79,3
Viscosit 40 °C	mm¿/s	11,4
Viscosit 100 °C	mm¿/s	135
Indice di viscosit	°C	-45
Punto di infiammabilit COC	°C	
Punto di scorrimento	°C	
Numero base totale	mgKOH/g	
Ceneri solfatate	%	